



- IEC C14 - IEC C15 Power Leads
- Fully Moulded Connector
- Available In Three Different Lengths
- H05RR-F Cable = 1m & 2m lengths
- H05RN-F Cable = 3m length
- IEC 60320 For C14 Plug & C15 Connector
- IEC 60245, VDE 0282-4 for H05RR-F & H05RN-F Cable

Product Features

- Connector C15 - IEC 60320
- Plug C14 - IEC 60320
- Cable H05RR-F & H05RN-F - IEC 60245, VDE 0282-4
- 10amp, 250volts

Product Description

The IEC C14 - IEC C15 Hot-Condition jumper cables are used for powering a variety of electrical appliances where heat can be an issue - e.g. Cisco Catalyst Switches, HP Procurve Switches and Dell PowerConnect Switches.

The connectors are moulded to provide a high-quality cable which is perfect for office and/or comms room use.

Part Codes	Descriptions
BC-C14-C15-1-BL	1m IEC C14 - IEC C15 Hot Condition Blue H05RR-F 0.75mm Power Leads
BC-C14-C15-2-BL	2m IEC C14 - IEC C15 Hot Condition Blue H05RR-F 0.75mm Power Leads
BC-C14-C15-3-BL	3m IEC C14 - IEC C15 Hot Condition Blue H05RN-F 1.0mm Power Leads